

EURa[®]
DRIVES

A DRIVES COMPANY

EURa Drives



Ad: No. 17 FUZHOU RD, YANTAI, ETDZ, SHANDONG, CHINA

Tel: 0086 4006866333

ENGLISH

www.euradrives.com

E800

FREQUENCY INVERTER

0.4 kW - 110 kW





E800

0.4 kW - 110 kW

FREQUENCY INVERTER

HIGHLIGHTS

All I/O channels programmable, two 12 Bit analogue inputs, to concatenate each other

Build in PID controller, with specific HVAC functions

MODBUS interface, for inverter control, and for reading and setting of all inverter I/O hardware channels

The inverter I/O hardware can be implemented in subordinated control systems

Control mode: V/Hz control for asynchronous motor, SENSORLESS control for Permanent Magnet Synchronous Motor - PMSM


Intelligent voltage, current and carrier frequency adjustment functions, "catch on the fly" function

PC-Software, for inverter control and programming, diagnosis and troubleshooting

Smart parameter copy tools

EMC filter (C3 class) integrated

FRAMESIZE



Inverter E800 - 1 x 230V / 240V

Model	Rated current	Frame-size	Dimensions (WxHxD-mm)	Brake resistor min. value
E800-0004 S2	0,4 kW - 2.5 A	E1	80x138x135	80 Ohm/200W
E800-0007 S2	0,75 kW - 4.5 A			
E800-0015 S2	1,5 kW - 7A	E2	106x180x150	
E800-0022 S2	2,2 kW - 10 A			

Inverter E800 - 3 x 400V / 460V

Model	Related current	Frame-size	Dimensions (WxHxD-mm)	Brake resistor min. value	
E800-0002 T3	0,2 kW - 0.6 A	E1	80x138x135	150 Ohm/80W	
E800-0004 T3	0,4 kW - 1.2 A				
E800-0007-T3	0,75 kW - 2 A			E2	106x180x150
E800-0015-T3	1,5 kW - 4 A				
E800-0022-T3	2,2 kW - 6.5 A	E3	106x180x150	150 Ohm/150W	
E800-0030-T3	3,0 kW - 7 A			150 Ohm/300W	
E800-0040-T3	4,0 kW - 9 A	E4	138x235x152	150 Ohm/400W	
E800-0055-T3	5,5 kW - 12 A			100 Ohm/550W	
E800-0075-T3	7,5 kW - 17 A	E5	156x265x170	100 Ohm/750W	
E800-0110-T3	11 kW - 23 A			100 Ohm/1.1kW	
E800-0150-T3	15 kW - 32 A	E6	205x340x196	50 Ohm/1.5kW	
E800-0185-T3	18,5 kW - 38 A			50 Ohm/2.0kW	
E800-0220-T3	22 kW - 44 A	C3	265x435x235	50 Ohm/2.2kW	
E800-0300-T3	30 kW - 60 A			25 Ohm/3.0kW	
E800-0370-T3	37 kW - 75 A	C4	315x480x234	25 Ohm/3.0kW	
E800-0450-T3	45 kW - 90 A			15 Ohm/4.5kW	
E800-0550-T3	55 kW - 110 A	C5	360x555x265	15 Ohm/5.5kW	
E800-0750-T3	75 kW - 150 A			15 Ohm/5.5kW	
E800-0900-T3	90 kW - 180 A	C6	410x630x300	8 Ohm/9.0kW	
E800-1100-T3	110 kW - 220 A	C6	410x630x300	Optional brake-unit	

TECHNICAL DATA

Power input	Supply voltage	1-Phase 220V ~ 240V (+/-15%) 3-Phase 380V-460 (+/-15%)
	Input frequency	44...67 Hz
	EMC filter	Integrated for second environment (industrial area) - option for first environment (residential area)
Motor output	Output voltage	0.....V-input
	Output frequency	0.5.....650 Hz
	Overload capability	120% - 60 sec / 15 min
Control-Mode	V/Hz	Linear, Variable torque curve, user programmable curve
	PWM frequency	800...10000Hz (FIXED / RANDOM)
Display	LED 7-segment display	Programmable, to display various inverter and working parameters
Control hardware (I/O)	Digital inputs	6 (8) dig. inputs (PNP/NPN)
	Analogue inputs	2 x 12 BIT analogue inputs 0...10V, 0(4)....20 mA)
	Analogue outputs	2 analogue output, to assign to various functions (0...10V, 0..20 mA)
	Digital outputs	2 digital outputs (free assignment to different functions)
	Relais	1 switchover contact 5 A 230 V (programmable function)
	MODBUS	Inverter control, reading and setting of all inverter I/O channels
Specials	Aux. power supply	Auxiliary power supply: 24V / 50 mA – on terminals 10V potentiometer power supply
Protection functions with Fault memory	Electrical protections	Overvoltage, undervoltage
	Thermal protections	Overcurrent, overload, motor overload, short circuit Inverter overtemperature, motor-overload I ² xt
Optionals and accessories	Display / keypad	Remote display / keypad unit
	Brake	Brake resistors for all kind of applications
	PC-Link Software	Smart tool for parameter setting, control an diagnosis
	Fieldbus	Gateway modules for all commonly used bus technologies
Environmental and operating conditions	Parameter copy stick	Smart tool for parameter storage and duplication
	Protection degree	IP20 / IP21 (option)
Environmental and operating conditions	Operating temperature	-10.....+40 °C
	Humidity	Max. 90 % non condensing, non corrosive
	Altitude	1000 m, above derating of 1% / 100m

LCD REMOTE KEYPAD FOR CABINET IP66



CABLE FOR REMOTE KEYPAD IP66

PARAMETER COPY STICK

